



Light Linear PT 4

Street and area lighting luminaires

LI-21XXX

IP65 · CLASS I · CE · IK07

Project :	Location :	Type :	Quantity :
Note :			

**Application**

Light Linear PT Street & Area lighting LED incorporates scalable light modules designed to be an aesthetic and economic alternative to high pressure sodium or metal halide street lantern. Excellent optic product technology delivers industry leading optimized target illumination performance. Light Linear PT is available type II, III and IV optic which provides a broad spread light distribution. Dark sky compliant. The fitting sleek, low profile shape. Main application for lighting of public, private roadways, car parks, exhibition areas.

Description

The luminaire rated as CLASS I with integral driver. Colour temperature 3000K and 4000K, LED CRI >80 and life time 50,000 Hours.

Aluminium housing and pole with high corrosion resistance. Stainless steel fasteners in grade 316. Durable silicone rubber gasket and clear toughened glass. The housing and pole are powder coating with high corrosion resistance and chemical chromated protection.

A20891 Root mount kit accessory for installation.

Ordering guide sample

LI-21172	- T4	- W30	- A20891	Colour Temperature
Model No	Type	Colour	Accessory	W30 - Warm white 3000K
				W40 - Neutral white 4000K

Product Code


Model No.	Lamp	System Power W	Lumen lm	Colour	EEC	Distribution Type	Weight kg
<input type="checkbox"/> LI-21172 - T2 - W30	48 LED	110	6613	3000K	A+	Type 2	31.5
<input type="checkbox"/> LI-21172 - T3 - W30	48 LED	110	6822	3000K	A+	Type 3	31.5
<input type="checkbox"/> LI-21172 - T4 - W30	48 LED	110	6866	3000K	A+	Type 4	31.5
<input type="checkbox"/> LI-21172 - T2 - W40	48 LED	110	7563	4000K	A+	Type 2	31.5
<input type="checkbox"/> LI-21172 - T3 - W40	48 LED	110	7802	4000K	A+	Type 3	31.5
<input type="checkbox"/> LI-21172 - T4 - W40	48 LED	110	7852	4000K	A+	Type 4	31.5
<input type="checkbox"/> LI-21291 - T2 - W30	48 LED	156	11378	3000K	A++	Type 2	31.5
<input type="checkbox"/> LI-21291 - T3 - W30	48 LED	156	11605	3000K	A++	Type 3	31.5
<input type="checkbox"/> LI-21291 - T4 - W30	48 LED	156	11812	3000K	A++	Type 4	31.5
<input type="checkbox"/> LI-21291 - T2 - W40	48 LED	156	12093	4000K	A++	Type 2	31.5
<input type="checkbox"/> LI-21291 - T3 - W40	48 LED	156	12335	4000K	A++	Type 3	31.5
<input type="checkbox"/> LI-21291 - T4 - W40	48 LED	156	12555	4000K	A++	Type 4	31.5

Colour Code

<input type="checkbox"/> - 01	<input type="checkbox"/> - 02	<input type="checkbox"/> - 03	<input type="checkbox"/> - 05	<input type="checkbox"/> - 06	
Black RAL 9011	Dark Grey RAL 7043	White RAL 9003	Matt Silver RAL 9006	Bronze RAL 6014	RESET

Accessory

☐ Root mount kit (A20891)



Light Linear PT 4





Street and area lighting luminaires

LI-21XXX





IP65 · CLASS I · CE · IK07

Photometric





T2



T3



T4



Light symbol

