



## Light Linear PT 1

Bollards

## LI-1000X

IP65 · CLASS I · CE · IK07

Project :	Location :	Type :	Quantity :
Note :			



## Application

Light Linear PT Bollard LED incorporates scalable light modules designed to be an aesthetic and economic alternative to the high pressure sodium or metal halide lighting systems. Industry leading optical technology ensures that only the targeted areas are illuminated, reducing unwanted light trespass. Long service life and vandal resistance are the further characteristics of this compact bollard. Developed for lighting driveways, pathways and squares.

## Description

The luminaire rated as CLASS I with integral driver. Colour temperature 3000K and 4000K, LED CRI >80 and life time 50,000 Hours.

Aluminum housing and pole with high corrosion resistance. Stainless steel fasteners in grade 316. Durable silicone rubber gasket and clear toughened glass. The housing and pole are a powder coating with high corrosion resistance and chemical chromatinized protection.

Anchor bolt kit accessory for installation.

## Product Code

Model No.	Lamp	System Power W	Lumen lm	Colour	EEC	Distribution Type	Weight kg
<input type="checkbox"/> LI-10001 - T2 - W30	12 LED	28	1768	3000K	A+	Type 2	8.2
<input type="checkbox"/> LI-10001 - T3 - W30	12 LED	28	1783	3000K	A+	Type 3	8.2
<input type="checkbox"/> LI-10001 - T4 - W30	12 LED	28	1794	3000K	A+	Type 4	8.2
<input type="checkbox"/> LI-10001 - T2 - W40	12 LED	28	1884	4000K	A+	Type 2	8.2
<input type="checkbox"/> LI-10001 - T3 - W40	12 LED	28	1899	4000K	A+	Type 3	8.2
<input type="checkbox"/> LI-10001 - T4 - W40	12 LED	28	1911	4000K	A+	Type 4	8.2
<input type="checkbox"/> LI-10002 - T2 - W30	24 LED	55	3583	3000K	A+	Type 2	8.5
<input type="checkbox"/> LI-10002 - T3 - W30	24 LED	55	3546	3000K	A+	Type 3	8.5
<input type="checkbox"/> LI-10002 - T4 - W30	24 LED	55	3593	3000K	A+	Type 4	8.5
<input type="checkbox"/> LI-10002 - T2 - W40	24 LED	55	3818	4000K	A+	Type 2	8.5
<input type="checkbox"/> LI-10002 - T3 - W40	24 LED	55	3778	4000K	A+	Type 3	8.5
<input type="checkbox"/> LI-10002 - T4 - W40	24 LED	55	3829	4000K	A+	Type 4	8.5

## Ordering guide sample

LI-10001 - T4 - W30 - A11091			
Model No	Type	Colour	Accessory
<b>Colour Temperature</b>			
W30 - Warm white 3000K			
W40 - Neutral white 4000K			

## Accessory



☐ Anchor bolt kit (A11091)

## Colour Code

<input type="checkbox"/> - 01	<input type="checkbox"/> - 02	<input type="checkbox"/> - 03	<input type="checkbox"/> - 05	<input type="checkbox"/> - 06	
Black RAL 9011	Dark Grey RAL 7043	White RAL 9003	Matt Silver RAL 9006	Bronze RAL 6014	RESET

Light Linear PT 1





Bollards

LI-1000X





IP65 · CLASS I · CE · IK07

Photometric





T2



T3



T4



Light symbol



T2

T3

T4